

Classic inserto

4 STELLE ★★★★★

	10 Min.-Max	12 Min.-Max	14 Min.-Max
 kW	5,5 - 9,9	5,5 - 11,6	6,96 - 14,81
 kW	4,9 - 8,7	4,9 - 10,3	6,48 - 13,24
 %	89 - 88	89 - 88	93 - 89
 %	0,013 - 0,010	0,040 - 0,013	0,016 - 0,010
 kg/h	1,3 - 2,0	1,3 - 2,4	1,43 - 3,05
 kg	14	14	16
 h	10 - 7	10 - 6	10 - 5
 m³	200	240	300
 mm	H 600 x L 600 x P 680		
 v/Hz	230 - 50		
 W	120		
 Ø mm	80		
 kg	100		
	Inox AISI 304		
	NO		
	A+		

IT

- VENTILAZIONE FORZATA
- 5 POTENZE DI FUNZIONAMENTO
- TERMOSTATO DI SICUREZZA
- PREDISPOSIZIONE TERMOSTATO ESTERNO
- PRESSOSTATO DI SICUREZZA
- CRONOTERMOSTATO

GB

- FORCED VENTILATION
- 5 OPERATING POWER LEVELS
- SAFETY THERMOSTAT
- SUITABLE FOR EXTERNAL THERMOSTAT
- SAFETY MANOSTAT
- TIMER THERMOSTAT

FR

- VENTILATION FORCÉE
- 5 PUISSANCES DE FONCTIONNEMENT
- THERMOSTAT DE SÉCURITÉ
- PRÉDISPOSITION POUR THERMOSTAT EXTÉRIEUR
- PRESSOSTAT DE SÉCURITÉ
- CHRONOTHERMOSTAT

ES

- VENTILACIÓ FORZADA
- 5 POTENCIAS DE FUNCIONAMIENTO
- TELEMANDO DE SEGURIDAD
- PREDISPOSICIÓN PARA TERMOSTATO EXTERNO
- PRESOSTATO DE SEGURIDAD
- CRONOTERMOSTATO



Sistema
estraibile
Pull system
Système
extractible
Sistema
extraíble

OPTIONAL:



Telecomando



Wi-Fi + assistenza remoto



KIT Canalizzazione
Ø 60 Flex



Cornice 3 lati



Piedistallo



Cornice 4 lati